



ADATA – TAIWAN

Specifications						
Type	2ft			4ft		
Power Consumption	10W			20W		
Color Temperature	3000K	4000K	5700K	3000K	4000K	5700K
CRI	≥80			≥80		
Lumens	900 lm	1000 lm	1000 lm	1900 lm	2000 lm	2000 lm
Base type	G13			G13		
Beam angle	270°			270°		
Operating temperature	-20~+40°C			-20~+40°C		
Voltage	100 - 240V			100V~240V		
Frequency	50/60 Hz			50/60 Hz		
Lifespan (light source)	40,000 Hours			30,000 Hours		
Dimensions	ψ29.0 x ψ26.5 x 590mm			ψ29.0 x ψ26.5 x 1198mm		
Weight	120g			240g		
Material	Full plastic					

T8 Tubelight

Applications:

- Office buildings, shopping malls, restaurants, schools, homes, factories, and other locations

Product Features:

- Energy saving: Traditional lights generate a lot of heat. LED lamps convert power to light with maximum energy efficiency.
- Durability and longevity: Lifespan is several times longer than traditional fluorescents, with average life of 30,000 to 50,000 hours. Long-term use without the need for replacement results in reduced labor costs.
- Durable: Utilizes a durable epoxy body rather than a traditional glass tube.
- Convenient: Measurements are designed for optimal compatibility to easily replace traditional lamps.
- Super Eco-Friendly: Does not contain mercury or lead.
- Low heat output: This lamp operates at below 40°C at room temperature, whereas traditional fluorescent lamps normally run at 65°C to 70°C. The lamp's low heat output helps maintain room temperature and reduces the need for air conditioning